

## ETM-36-140-F

SPECIFICATIONS	STANDARD SCAN QR CODE	
Working height	13,7 m	ETM-36-140-F 3°/5° METERS 15
Platform height	11,7 m 🛄 🔅 🎲 🛄	14
Max Outreach at a 0° slope	8,6 / 7,9 m*	
Max Cage capacity	120 / 200 kg	
Flyboom		
GVW	5000 kg	
Max slope	5 / 10°	
STANDARD	OPTIONS	
Up-under Radial outriggers (short)	Up-under Radial outriggers (long)**	
2 man Euro cage (with door, flash and electrical outlet)	Patented Axle locking system	
Rear platform (steel)	LSO: Load Sensing Outreach/CANbus	
FPC: Full Proportional CANbus controls with display	Home function & limited work area without outriggers	10 9 8 7 6 5 4 3 2 1 0 1 2 3 4 5 6 7 8 9 10
1 kV Insulation	Drive option	D. L. (200 / 200 L
	Dive option	Reach at 120 / 200 kg cage load <sup>or</sup>
IMAGES		
Rear platform (cage stowed asymmetrically)***	Flash on turret	
Fortime workshop interior (optional)	Up-under Radial outriggers	Limited work area without outriggers (optional)
We have a state of the state of th	FPC: Full proportional CANbus controls with display	Walk Through System": Direct access to cage from cabin (optional)   * Walk Through System": Direct access to cage from cabin (optional)   * Papending on the vehicle   * Cage capacity expanded to 230 kg with long outriggers   ** Standard: Steel rear platform. Optional: Aluminium (-30 kg)
TIME International A/S Søndervang 3 - DK-9640 Farsø Phone +45 9863 2433 - Fax +45 9863 2483 sales@TeamTIME.dk - www.TeamTIME.dk	VERSALIFT.	ETM-36-140-F/v234/MB Sprinter / VW Crafter/2014-03/UK